

UNCLASSIFIED



CISCO ACI STIG REVISION HISTORY

05 January 2026

Developed by Cisco and DISA for the DOD

UNCLASSIFIED

REVISION HISTORY		
Document Revised	Description of Change	Release Date
Cisco ACI Layer 2 Switch STIG, V1R1	Cisco ACI Layer 2 Switch STIG, V1R2: <ul style="list-style-type: none"> - CACI-L2-000001 - Updated navigation in Check and Fix. - CACI-L2-000002, CACI-L2-000004, CACI-L2-000009, CACI-L2-000010, CACI-L2-000011 - Changed to Not Applicable. VTP is out of scope for Cisco ACI since the protocol is not used for VLANs. - CACI-L2-000005 - Updated Discussion. - CACI-L2-000014 - Changed to Not Applicable. No configuration or VLAN is assigned in ACI to any interface without configuration, so even in the case where an interface is brought up by mistake, no traffic will be passed through that interface. - CACI-L2-000015, CACI-L2-000016, CACI-L2-000018 - Removed requirement as it requires the configuration of EPG, Bridge Domains, VRFs and Tenants, which is covered in the Router STIG as part of the L3 configuration. - CACI-L2-000017 - Updated navigation in Check and Fix. Updated Vulnerability Discussion. - CACI-L2-000019 - Removed requirement as it requires OOB configuration, configured in the Router STIG at layer 3. 	05 January 2026
Cisco ACI NDM STIG, V1R1	Cisco ACI NDM STIG, V1R2: <ul style="list-style-type: none"> - CACI-ND-000001 - Updated check and fix. As of version 6.0, the settings for date/time are under System >> System Settings. - CACI-ND-000003 - Removed references to HTML option for banner display in Check and Fix. - CACI-ND-000004 - Updated Check and Fix navigation. - CACI-ND-000005 - Updated navigation instructions and added reference to OOB ports in Check and Fix. - CACI-ND-000007, CACI-ND-000009, CACI-ND-000029, CACI-ND-000043, CACI-ND-000045 - Updated navigation instructions in Check and Fix. 	

REVISION HISTORY		
Document Revised	Description of Change	Release Date
Cisco ACI Router STIG, V1R1	<ul style="list-style-type: none"> - CACI-ND-000011 - Updated Fix to remove cli method. - CACI-ND-000012 - Updated second paragraph in Discussion. Updated navigation in Check and Fix. - CACI-ND-000016 - Updated Check and Fix to remove cli method. - CACI-ND-000054 - Updated Fix to remove cli method. Updated navigation in Check text. - CACI-ND-000056, CACI-ND-000060 - Updated navigation instructions for Fix. <p>Cisco ACI Router STIG, V1R2:</p> <ul style="list-style-type: none"> - CACI-RT-000001 - Updated navigation for Check and Fix to remove CLI commands. Combined with SRG-NET-000019-RTR-000005. - CACI-RT-000002, CACI-RT-000003, CACI-RT-000004 - Updated navigation for Check and Fix to remove CLI commands. Added note to Fix and Vulnerability Discussion. - CACI-RT-000005, CACI-RT-000006, CACI-RT-000007, CACI-RT-000025, CACI-RT-000037, CACI-RT-000039 - Changed to Not Applicable. Cisco ACI is not a Multicast Source Discovery Protocol (MSDP). - CACI-RT-000008 - Updated to Inherently Met. PIM is disabled by default on all interfaces that are not required to support multicast routing and this behavior cannot be changed. - CACI-RT-000009 - Updated Check and Fix to use GUI configuration. - CACI-RT-000010, CACI-RT-000042 - Combined with CACI-RT-000001. Removed from STIG. - CACI-RT-000011, CACI-RT-000012 - Changed status to Not Applicable. The Cisco ACI is not an out-of-band management (OOBM) gateway. - CACI-RT-000013, CACI-RT-000014, CACI-RT-000016, CACI-RT-000017, CACI-RT-000018, CACI-RT-000019, CACI-RT-000021, CACI-RT-000022, CACI-RT-000027, CACI-RT-000028, CACI-RT-000029, CACI-RT-000031, CACI-RT-000032, CACI-RT-000035, 	

REVISION HISTORY		
Document Revised	Description of Change	Release Date
	<p>CACI-RT-000038, CACI-RT-000041, CACI-RT-000043, CACI-RT-000044 - Updated navigation and configuration steps in the Check and Fix.</p> <p>- CACI-RT-000020 - Changed to Not Applicable because it is configured as part of the First Hop Security policy by default.</p> <p>- CACI-RT-000023, CACI-RT-000024 - Combined with CACI-RT-000018. Removed from STIG.</p> <p>- CACI-RT-000030 - Combined with CACI-RT-000031. Removed from STIG.</p> <p>- CACI-RT-000033 - Updated to Inherently Met. Default is 180 and it cannot be changed or reconfigured, which meets the requirement.</p> <p>- CACI-RT-000034 - Changed the requirement to match the vendor recommended alternative configuration. Updated the Vulnerability Discussion, Check, and Fix.</p> <p>- CACI-RT-000036 - Combined with CACI-RT-000035. Removed from STIG.</p> <p>- CACI-RT-000040 - Changed to Does Not Meet based on vendor feedback. The product default is 64 and it cannot be changed. There is no mitigation at this time.</p> <p>- CACI-RT-000045 - Changed to Not Applicable. ACI does not support RSVP or MPLS in normal functions.</p>	
- NA	- Initial Release.	27 May 2025